





WOOD COATINGS

MasquePrimer 10

PRODUCT CODE: 6910315



DESCRIPTION

MasquePrimer 10 is a high-end water based industrial primer for new untreated wood designated for exterior use (use classes 2-3) as defined in BS/EN 335-1 such as windows and doors and protects the wood surface and the treated area against wood destroying and wood discolouring fungi.

MasquePrimer 10 offer a perfect balance between equalisation and transparency and is therefore the perfect choice when a high-quality translucent appearance is required.

The product has been formulated to provide good run-off properties and leaves a homogenous, smooth surface with minimum of wood fibre rising perfectly ready for subsequent mid- and/or top coats.

By use of MasquePrimer 10 the wood becomes more dimensional stable.

COLOR

MasquePrimer 10 is available in an almost unlimited numbers of translucent colours.

Colours can be tinted in our highly innovative and automated tinting systems ensuring fast and reliable deliveries of even small batches.

GLOSS LEVEL AND TECHNICAL DATA

-

Technical Data:

Density: 1.000 – 1.020 g/cm³

% Solids: 6 – 7 %

APPLICATION

Pre-treatment: The wood must be clean and free from wood dust and contamination. The moisture content of the wood should be approx. 13 % and should not exceed 15 %.

Application: Flow coating, dipping, in brush machine, in vacuum or by manual brush/cloth

Application conditions: The product is delivered ready for use but due to evaporation under processing the solid content of the product must be adjusted with water regularly.

Stir the product well before use. Optimum temperature for products and surroundings: 18-22 °C with relative air humidity of approx. 50 %

INDUSTRIAS QUÍMICAS MASQUELACK S.A.

DRYING

Drying times are indicative at 20 °C and 50% relative humidity

Dry to handle/recoat: App. 1-2 hours

The drying time can be reduced by use of force drying systems and efficient ventilation

CONSUMPTION

Depending to wood quality and application methods.

CLEANING OF EQUIPMENT

The equipment can be cleaned with water

STORAGE/TRANSPORT

Temperature for storage/transportation: between 5 – 25 °C
Keep containers tightly closed after use.

PACKAGING

Delivered in drums and IBC containers.

DISPOSAL OF WASTE

See information in the Section 13 of the Safety Data Sheet

SAFETY DATA

More information and relevant data are stated in Safety Data Sheet according to 1907/2006/CE (REACH) and 2015/830/EU.
Classified and Labelled according to 1272/2008 (CLP)

The given information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Masquelack.



INDUSTRIAS QUÍMICAS MASQUELACK S.A.