





# MasqueWoodPro

PRODUCT CODE: 8832037



## DESCRIPTION

MasqueWoodPro is an aqueous industrial wood preservative for new untreated wood designated for exterior use as defined in BS/EN 335-1:1994 such as windows and doors.

The product protects the wood surface and the treated area against wood destroying and wood discolouring fungi and satisfies the performance requirement of EN 599-1. Furthermore, the wood become more dimensional stable.

MasqueWoodPro minimizes patchiness in subsequent translucent surface treatment.

## COLOR

Colorless

## GLOSS LEVEL AND TECHNICAL DATA

N.A.

### Technical Data:

Density: 1.000 – 1.040 g/cm<sup>3</sup>

% VOC: 4 – 6 %

## APPLICATION

**Pre-treatment:** The wood must be clean and free from wood dust and contamination. The moisture content of the wood should be approx. 13 % and should not exceed 15 %.

**Application:** Brush, dipping or flow coating. It can also be applied by spraying.

**Application conditions:** The product is delivered ready for use but due to evaporation under processing the solid content of the product must be adjusted with water regularly.

Stir the product well before use. Optimum temperature for products and surroundings: 18-22 °C with relative air humidity of approx. 50 %

INDUSTRIAS QUÍMICAS MASQUELACK S.A.

C/ De Pedrosa, 26-28. 08783 Masquefa – Barcelona – España -  
masquelack@masquelack.com – [www.masquelack.com](http://www.masquelack.com)

Representative in Lithuania – Refor UAB, Raudondvario pl. 242C, LT-47158, Kaunas – [www.refor.lt](http://www.refor.lt)



## DRYING

---

Physical

Dry to handle: 1 – 2 hours  
Dry to recoat: 2 – 3 hours

The drying time can be reduced by use of force drying systems and efficient ventilation

## CONSUMPTION

---

Depending to wood quality and application methods.

## CLEANING OF EQUIPMENT

---

The equipment can be cleaned with water or using our thinner WB AQUANET Concentré (Code: 8196040)

## STORAGE/TRANSPORT

---

Temperature for storage/transportation: between 5 – 25 °C

Température de transport: La température pendant toute la durée de la livraison doit être supérieure à 5 °C.

## PACKAGING

---

Delivered in drums and IBC containers.

## DISPOSAL OF WASTE

---

See information in the Section 13 of the Safety Data Sheet

## SAFETY DATA

---

More information and relevant data are stated in Safety Data Sheet according to 1907/2006/CE (REACH) and 2015/830/EU.

Classified and Labelled according to 1272/2008 (CLP)

The given information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Masquelack.

---

### INDUSTRIAS QUÍMICAS MASQUELACK S.A.

C/ De Pedrosa, 26-28. 08783 Masquefa – Barcelona – España -  
masquelack@masquelack.com – [www.masquelack.com](http://www.masquelack.com)

Representative in Lithuania – Refor UAB, Raudondvario pl. 242C, LT-47158, Kaunas – [www.refor.lt](http://www.refor.lt)

## INFORMATION ON MANDATORY LABELLING FOR ITEMS TREATED WITH MasqueWoodPro

When an item has been treated with wood preservative and its biocidal properties (protection against e.g. wood destroying or discolouring fungi) are claimed, below instructions, which are in accordance with the European Biocidal Products Directive, effective as of 1 September 2013, must be followed:

The person responsible for the sale of treated items such as doors and windows shall label such items with the details stated here for MasqueWoodPro in the FACT SHEET below.

Labelling shall be clearly visible, easily legible and of suitable permanence. When necessary due to size of function of treated item, labelling shall be printed on the packaging, the user guide or on the guarantee.

For further details, please refer to the Biocides Regulation, 528/2012 Article 58, part 3:

<https://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2012:167:0001:0123:EN:PDF>

### FACT SHEET for MasqueWoodPro treated items

<b>This item has been treated with wood preservative: (Regulated by the Biocides Regulation 528/2012, PT8)</b>	MasqueWoodPro
a) Items treated with MasqueWoodPro contain:	Biocides approved for product type 8
b) Items treated with MasqueWoodPro are protected against:	Wood destroying or discolouring fungi
c) Items treated with MasqueWoodPro contain the following biocides:	Propiconazole, IPBC
d) Items treated with MasqueWoodPro contain the following nanomaterials:	-
The wood preservative MasqueWoodPro is produced by:	Industrias Químicas Masquelack S.A., C. La Pedrosa 26-28, 08783 Masquefa (Spain)

#### e) Special precautions for items treated with MasqueWoodPro:

**The surface of the wood must be coated with e.g. varnish or paint. Coating of the surface must be carried out at regular intervals.**

The given information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Masquelack.

INDUSTRIAS QUÍMICAS MASQUELACK S.A.

C/ De Pedrosa, 26-28. 08783 Masquefa – Barcelona – España -  
masquelack@masquelack.com – [www.masquelack.com](http://www.masquelack.com)

Representative in Lithuania – Refor UAB, Raudondvario pl. 242C, LT-47158, Kaunas – [www.refor.lt](http://www.refor.lt)

